

RECEIVED
CENTRAL FAX CENTER

FEB 05 2008

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) ~~An apparatus for guiding a door leaf of a~~ A sliding door comprising:

a door leaf having a front surface and an edge surface extending perpendicular to the front surface;

a guide surface for guiding the door leaf, the guide surface being generally parallel to the front surface of the door leaf;

at least one guide element having an axis of rotation extending generally perpendicular to the edge surface; and

a movable belt engaging said the at least one guide element, ~~said movable belt and having a portion adapted for contact with a~~ which contacts the guide surface associated with the door leaf whereby when said at least one guide element is mounted on an edge surface of the door leaf to extend generally parallel to a plane of the guide surface with said axis of rotation extending generally perpendicular to a plane of said edge surface, ~~said portion of said movable belt contacts the guide surface during sliding of the door leaf in a plane generally parallel to the plane of the guide surface.~~

2. (Currently Amended) The door according to claim 1 wherein the guide surface is disposed in a region of a door frame or a door case for the door leaf and said the at least one guide element is attached to the edge surface of the door leaf.

3. (Currently Amended) The door according to claim 1 wherein the guide surface is disposed in the door leaf and said the at least one guide element is attached to a region of a door frame or a door case for the door leaf.

4. (Withdrawn) The door according to claim 1 wherein the guide surface is a pair of facing guide surfaces and including at least another guide element mounted to extend generally parallel to the plane of the door leaf and another movable belt engaging said at least another guide element and having a portion contacting one of the facing guide surfaces during sliding of said door leaf relative to the facing guide surfaces.

5. (Currently Amended) The door according to claim ~~1~~ 2 wherein ~~said~~ the at least one guide element is a roller rotatably attached to the door leaf.

6. (Currently Amended) The door according to claim 1 wherein ~~said~~ the at least one guide element holds ~~said~~ the movable belt against the guide surface.

7. (Currently Amended) The door according to claim 1 wherein ~~said~~ the movable belt seals against the guide surface to prevent air leakage between opposite sides of the door leaf.

8. (Withdrawn) The door according to claim 1 including means for restricting movement of said movable belt laterally relative to the guide surface.

9. (Currently Amended) The door according to claim 1 wherein ~~said~~ the movable belt has resilient properties.

10. (Currently Amended) The door according to claim 1 wherein ~~said~~ the movable belt has a laminated structure.

11. (Currently Amended) A door used in an elevator installation comprising:
at least one elevator door leaf having a front surface and an edge surface extending perpendicular to said front surface in a plane;
at least one guide element mounted on said edge surface and having an axis of rotation extending generally perpendicular to ~~the~~ a plane of said edge surface; and
a movable belt engaging said at least one guide element, said movable belt having a portion adapted for contact with a guide surface during sliding of said at least one elevator door leaf relative to the guide surface, said guide surface extending in a plane generally perpendicular to the plane of said edge surface.

12. (Previously Presented) The door according to claim 11 including another guide element mounted on said edge surface and having an axis of rotation extending generally perpendicular to the plane of said edge surface and said movable belt being an endless belt engaging said another guide element.

13. (Withdrawn) The door according to claim 11 wherein said movable belt has a first end fixed to said at least one elevator door leaf and a second end fixed relative to the guide surface.

14. (Withdrawn) The door according to claim 11 wherein at least one said guide element includes a belt guide portion engaging said movable belt and having a first diameter, a lower end plate attached at a lower end of said belt guide portion and having a second diameter larger than said first diameter, and an upper portion attached at an upper end of said belt guide portion and having a third diameter larger than said first diameter.

15. (Withdrawn) The door according to claim 14 including a roller bearing mounted in said at least one elevator door leaf and rotatably retaining said upper portion of said at least one guide element.

16. (Withdrawn) The door according to claim 11 wherein said at least one guide element is adapted to extend into narrowed portions of a groove above and below the guide surface for restricting movement of said belt laterally relative to the guide surface.

17. (Withdrawn) A sliding door comprising:

at least one door leaf;

a pair of spaced apart first guide elements mounted to extend generally parallel to a plane of said at least one door leaf;

a first movable belt engaging said first guide elements and having a portion adapted for contact with a first guide surface during sliding of said at least one door leaf;

a pair of spaced apart second guide elements mounted to extend generally parallel to the plane of said at least one door leaf; and

a second movable belt engaging said first guide elements and having a portion adapted for contact with a second guide surface during sliding of said at least one door leaf, said first and second movable belts being in contact.